

Resato high pressure gauges



Example PBX-xxx-LH series

Specifications

Main features:

- ✓ Case: Ø 63 mm or Ø 100 mm or Ø160 mm.
- ✓ Ranges: 0-60 bar up to 0-7000 bar.
- ✓ Ranges: 0-1000 psi up to 0-100,000 psi.
- ✓ Glycerin filled (L).
- ✓ Window: safety glass.
- ✓ Dial: aluminum, black figures on white background
- ✓ Pointer: aluminum black.
- ✓ Connection: lower back M16x1,5-HP-Female.
- ✓ Accuracy: $\pm 1,0\%$ (< 1000 bar) or $\pm 1,6\%$ (> 1000 bar).
- ✓ Mounting: u-clamp panel mounted (H) Calibration certificate.
- ✓ Gauges >2000 bar/ 30,000 psi solid front



Standard models

Model	Accuracy	Case (mm)
PBX-063-LH	1,6%	063
PBX-100-LH	1,0%	100
PBX-160-LH	1,0%	160
PBX-SF-100-LD	1,6%	100
PBX-SF-HP-160-LD	1,6%	160

Options:

- ✓ Double scale.
- ✓ Accuracy 0,6% for Ø 100 and Ø160 up to 1000 bar / 15,000 psi
- ✓ Red drag pointer.
- ✓ Direct mounted (D).
- ✓ Bottom connection.
- ✓ Double measurement system
- ✓ Cushioning.